Integra

STERED NETWORK A/V RECEIVER



Bask in the dynamic energy of music powered by Integra stereo amplification. Enjoy a wealth of nextgeneration audio options at your fingertips together with generous connectivity for your all your source components.

ADVANCED FEATURES

- 4 HDMI Inputs / 1 Output Supporting 4K / 60 Hz, Dolby Vision[™], HLG (Hybrid Log Gamma)¹, HDR10, WCG (Wide Color Gamut), and BT.2020 Pass-through with HDCP 2.2
- AKM AK4438 384 kHz / 32-bit Hi-Grade DAC
- · VLSC™ Technology for Noise-free Signal Path
- · Dual-band 5 GHz / 2.4 GHz Wi-Fi® Certified Wireless LAN Capability
- Bluetooth Version 4.1+LE
- (Profile: A2DP v1.2, AVRCP v1.3, HOGP-Host (Client), HOGP-HID Device (Server), HID Service (HIDS))
- \cdot Chromecast built-in'', DTS Play-Fi^{ie''} and FlareConnect for Wireless Multi-room Audio Streaming Capability and Flexibility
- Apple AirPlay® Support for Wireless Music Streaming
- Control and Stream Network Audio with Free Integra Control Pro App for iOS and Android™ Devices*²
- \cdot Internet Radio and Music Streaming Services Including TIDAL, Spotify, TuneIn Radio, Pandora®, and Deezer*3
- · Hand-selected Audio-tuned Parts
- · Low-Impedance Amplification System for Dynamic and Powerful Performance
- · Fully Discrete Output Stage Circuitry
- · Massive EI High-Power Transformer
- · Two Custom-made Capacitors
- Non-Phase-Shift Amp Design for Realistic Sound Imaging
- · Supports Hi-Res Audio Playback Including DSD 5.6 MHz, and 192 / 24 PCM
- \cdot Decodes FLAC, WAV, ALAC, DSD, AIFF, WMA Lossless, MP3, and AAC via Network / USB
- Direct Listening Mode for Clear Signal Playback
- · High-Definition Graphical User Interface via HDMI
- · A/V Sync Control (Up to 500 ms in 5 ms Steps at 48 kHz)
- · Crossover Adjustment
- 40 / 45 / 50 / 55 / 60 / 70 / 80 / 90 / 100 / 110 / 120 / 130 / 150 / 180 / 200 Hz
- · Subwoofer Out
- · Speaker A / B Drive for Additional Installation Flexibility

*1 Requires firmware update. *2 Please consult App Store or Google Play™ for minimum OS and device requirements. *3 Availability of services depends on region.

OTHER FEATURES

- · 100 Watts per Channel at 8 Ohms, 20 Hz–20 kHz, 0.08 % THD, 2 Channels Driven, FTC
- · 3 Digital Audio Inputs (2 Optical and 1 Coaxial)
- · 3 Analog Audio Inputs (Excluding Phono Input)
- Phono Input (MM) for Turntable Connection
- · Subwoofer Pre Out (x 2)
- · Front USB Input (1 A / 5 V) for Audio Playback via USB Storage Devices
- · Rear USB Input (500 mA / 1 V) to Power Media Streaming Dongles
- · Gold-Plated Quarter-inch Headphone Jack
- · Transparent High-Grade Banana Plug-Compatible Speaker Terminals
- · High-Quality Gold-Plated RCA Terminals to Eliminate Surface Corrosion and Oxidation
- Anti-Resonant Aluminum Front Panel and Volume Control
- Independent Bass, Treble, and Balance Controls
- · 3-Mode Display Dimmer (Normal / Dim / Dimmer)
- · 40 FM / AM Random Presets
- Preset Station Naming (Up to 10 Characters)
- · Sleep Timer, HDMI Passthrough, and Network Standby
- Full-Function RI Remote Control

CUSTOM INTEGRATION FEATURES

· Bi-Directional RS232 and Ethernet Control Port for Home Automation

- · Zone 2 Line Out for Distributed Audio Playback in Another Room
- · Zone 2 DAC for NET and USB Sources
- · Dealer Settings Memory Store and Recall
- · IR Input and 1 Output
- 2 Programmable 12 V Triggers (100 mA, 25 mA, with Adjustable Delay)
 Optional Rack-Mount Kit Available (IRK-130-3B)

Integra.

DTM-7

STERED NETWORK A/V RECEIVER

Hi·Res AUDIO

DSD HOMI

\/LSC 384 KHZ 32 bit

(((ZONEZ)))



AirPlay

BiPod I iPhone I iPad

Chromecast built-in

Play-Fi

♦ Flare connect

Bluetooth

pandora

*** TIDAL

DEEZER

Spotify

+ tunein

USB

RI





-

SPECIFICATIONS AMPLIFIER SECTION Power Output

i onoi output	
All Channels :	100 W/Ch at 8 Ohms, 20 Hz–20 kHz, 0.08 % THD, 2 Channels Driven, FTC
Dynamic Power :	240 W (3 Ohms, Front) 210 W (4 Ohms, Front) 120 W (8 Ohms, Front)
THD+N (Total Harmonic Distortion + Noise) :	0.08% (20 Hz-20 kHz, Half Power)
Input Sensitivity and Impedance :	200 mV / 47 k-Ohms (Line) 3.5 mV / 47 k-Ohms (Phono MM)
Rated RCA Output Level and Impedance :	1.0 V / 470 Ohms (Subwoofer Pre Out) 200 mV / 2.3 k-Ohms (Zone Line Out)
Phono Overload :	70 mV (MM 1 kHz 0.5%)
Frequency Response :	10 Hz-100 kHz / +1 dB, -3 dB (Direct Mode)
Tone Control :	±10 dB, 90 Hz (Bass) ±10 dB, 7.5 kHz (Treble)
Signal-to-Noise Ratio :	106 dB (Line, IHF-A) 80 dB (Phono MM, IHF-A)
Speaker Impedance :	4 Ohms-16 Ohms
Headphone Output Impedance :	330 Ohms
Headphone Rated Output :	80 mW (32 Ohms 1 kHz 10 % THD)

TUNER SECTION Tuning Frequency Range :

FM / AM Preset Memory :

GENERAL Power Supply : Power Consumption : Standby Power Consumption : No-Sound Power Consumption : Network Standby Power Consumption : 2.6 W

Dimensions (W x H x D) :

Weight :

CARTON


Dimensions (W x H x D) :


Weight :


FM 87.5 MHz-107.9 MHz AM 530 kHz-1,710 kHz 40 stations

AC 120 V~, 60 Hz 260 W 0.1 W 35 W 17 1/8" x 5 7/8" x 12 15/16" (435 x 149.5 x 328 mm) 18.7 lbs. (8.5 kg)

21 13/16" x 9 1/2" x 15 13/16" (554 x 242 x 401 mm) 23.1 lbs. (10.5 kg)







Due to a policy of continuous product improvement, Integra reserves the right to change specifications and appearance without notice. For DTS patents, see http://patents.dts.com. Manufactured under license from DTS, Inc. DTS, Play-Fi, the Symbol, and Play-Fi together in combination with the Symbol are trademarks of DTS, Inc. DTS and Play-Fi are registered trademarks of DTS, Inc. © DTS, Inc. All Rights Reserved. The terms HDMI, the HDMI logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. The Bluetooth® word mark and logos are rowned by the Bluetooth S(5, Inc. All, Pad, IPAO, IPAO

INSPIRED BY PASSION - DRIVEN BY EXCELLENCE WWW.INTEGRAHOMETHEATER.COM